

TASKalfa 408ci

DO MORE
WITH A4.

The TASKalfa 408ci is a powerful A4 colour MFP for small to medium sized workgroups in medium to large corporate environment where durable operations and flexible finishing are required. A renewed 7" operation screen with intuitive operation such as scroll and slide, pinch in/pinch out like smartphones and tablets. Advanced security functionality like secure boot, Trusted Platform Module (TPM) and standard Data Security Kit.

- ▶ A4 Colour Multifunctional
- ▶ 40 ppm in Colour/Monochrome
- ▶ 1200 x 1200 dpi resolution



The TASKalfa 408ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 408ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

Standard Specifications

GENERAL

KYOCERA TASKalfa Laser Colour Multifunctional, HyPAS™ solution platform

Operation panel: Smart intuitive new user interface, 177.8mm (7 inch) full-colour touch panel with scroll and slide smartphone/tablet operability, 0–90° swivel mounted

Engine speed: Up to 40 pages A4 per minute, Duplex print speed: 40 pages A4 per minute

Resolution: 1,200 × 1,200 dpi print at reduced speed, multibit technology for print quality of up to 9,600 × 600 dpi (print), 600 × 600 dpi (scan/copy)

Warm-up time: Approx. 21.8 seconds or less

Time to first print: Approx. 5.4/6.4 seconds or less in Monochrome/Colour

Time to first copy: Approx. 5.8/6.9 seconds or less in Monochrome/Colour (Platen)

CPU: Freescale QorIQ T1042 (Quad Core) 1.0 GHz

Memory: 4 GB RAM, 8 GB SSD, 320 GB HDD

Standard interfaces: 3 × USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), USB 2.0 (Hi-Speed), 2 eKUIO slots for optional internal

print server, fax system, slot for optional SD Card, NFC tag

Integrated accounting: 1,000 department codes

Dimensions (W × D × H): 550 mm × 508 mm × 612.8 mm

Weight: 49.3 kg

Power source: AC 220–240 V, 50/60 Hz

Power consumption: Copy/Print Mode: Mono 652 W/Color 652 W; Low Power Mode: 52 W; Ready Mode: 84 W; Sleep Mode: 0.7 W

Noise (sound pressure level: ISO 7779/ISO 9296):

Copying/Printing: 68.2 dB(A) LpA

Stand-by: 45 dB(A) LpA

Safety standards: This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Multi-purpose tray: 100 sheets, 60–220 g/m² (Banner 129–163 g/m²), A4, A5, A6, B5, B6, Letter, Legal, Custom (70 × 148 to 216 × 356 mm), Banner max. 216 × 1,220 mm; Standard universal paper cassette: 500 sheets, 60–220 g/m², A4, A5, A6, B5, B6, Letter, Legal, Custom (105 × 148 to 216 × 356 mm);

Max. input capacity with options: 3,100 sheets A4

Duplex: Standard Duplex unit: 60–220 g/m², A4, A5, B5, Letter, Legal

Output capacity: Standard 500 sheets face-down with paper full sensor

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc

Emulations: PCL6 (PCL-XL/PCL-5c), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

PRINT FUNCTIONS

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Wi-Fi Direct, Google cloud print, DSK standard

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality

COPY FUNCTIONS

Max. original size: A4/Legal

Continuous copying: 1–9,999

Zoom range: 25–400 % in 1 % steps

Preset magnification ratios: 5 Reductions/5 Enlargements

Exposure mode: Auto, manual: 9 steps

Image adjustments: Text + Photo, Photo, Text, Map, Printed document

Features: Scan-once-copy-many, electronic sort (collate), ID card copy, 2in1, 4in1, auto cassette change, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Network TWAIN, WIA, WSD scan

Scan speed: DP-5100 up to 60 ipm; DP-5120 up to 120 ipm; DP-5130 up to 170 ipm

Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per colour

Max. scan size: A4, Legal, Banner up to 1,900 mm

Original recognition: Text, photo, text + photo, light text/fine line, optimised for OCR

File types: TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPG compression/high compression PDF), Searchable PDF (Option), MS Office file (Option)

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3

Fax Memory: 170 MB

Modem speed: Max. 33.6 kbps

Transmission time: Max. 3 seconds (JBIG)

Scanning speed: 2.0 seconds or less

Address book: 2,000 entries

Fax resolution:

Normal: 8 dot/mm × 3.85 line/mm (200 × 100 dpi)

Fine: 8 dot/mm × 7.7 line/mm (200 × 200 dpi)

Superfine: 8 dot/mm × 15.4 line/mm (200 × 400 dpi)

Ultrafine: 16 dot/mm × 15.4 line/mm (400 × 400 dpi)

600 × 600 dpi

Halftone: 256 greyscales

Maximum original size: A4/Legal, Banner up to 1,600 mm

Compression method: JBIG, MMR, MR, MH

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with 5 % coverage A4.

TK-5315K Toner Kit: Microfine toner black for 24,000 pages A4

TK-5315C, TK-5315M, TK-5315Y Toner Kit: Microfine toner cyan, magenta, yellow for 18,000 pages A4

CONSUMABLES

WT-5191 Waste Toner Bottle: 44,000 sheets (in accordance with 5 % coverage; Monochrome/Colour=7:3)

Staples: SH-10 for DF-5100/DF-5110/DF-5120, 3 × 5,000

OPTIONS

Fax System 10 (X): max. 2: Super G3 Fax, network Fax

Internet Fax Kit (A): Option for Fax System 10(X), T.37 via SMTP/ POP3 server

DP-5100 Reverse Document Processor: 75 sheets, 50–120 g/m²

DP-5120 Dual Scan Document Processor: 100 sheets, 50–120 g/m²

DP-5130 Dual Scan Document Processor: 270 sheets with double feed detection, staple detection, 50–120 g/m²

PF-5120 Paper feeder: 500 sheets, 60–220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 × 148 mm to 216 × 356 mm)

PF-5130 Paper feeder¹: 2 × 500 sheets, 60–220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 × 148 mm to 216 × 356 mm)

PF-5140 Paper feeder¹: 2,000 sheets, 60–220 g/m²; A4, Letter

DT-5100 Document tray: To place originals or USB Keyboard

JS-5100 Job separator: 100-sheet internal job separator, 60–220 g/m²; A6–A4, Legal

MT-5100 5-Bin Mailbox sorter²: 5 bins × 100 sheets A4, 60–163 g/m², Main tray: 500 sheets A4, 60–220 g/m²

DF-5100 Internal Document Finisher: 300 sheets 60–220 g/m², Stapling up to 50 sheets A4 at 2 positions

DF-5110 External Document Finisher²: 1,000 sheets 60–220 g/m², Stapling up to 50 sheets A4 at 2 positions

PH-5110 Punch Unit: for DF-5110, 2-hole/4-hole, 60–220 g/m², A4

DF-5120 External Document Finisher²: 3,000 sheets 60–220 g/m², Stapling up to 50 sheets A4 at 2 positions

Punch unit included: 2-hole/4-hole, 60–220 g/m², A4

Sub tray: Max. 200 sheets A4, 60–220 g/m²

UG-33: ThinPrint support

UG-34: Emulation (IBM Proprinter/EPSON LQ-850/ LinePrinter)

USB IC Card Reader + Card Authentication Kit (B):

Supports various authentication card keys

IC Card Reader Holder 11: To integrate the USB IC Card

Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx)

Optional interfaces:

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)

IB-51: Wireless LAN (802.11b/g/n)

IB-35: Direct Wi-Fi Interface

NK-7100(B): Numeric keypad

CB-5110H Cabinet: Wooden desk with storage capacity, approx. 55 cm × 51 cm × 50 cm (W × D × H)

CB-5110L Cabinet: Wooden desk with storage capacity, approx. 55 cm × 51 cm × 34 cm (W × D × H)

CB-5120H Cabinet: Metal desk with storage capacity, approx. 55 cm × 51 cm × 50 cm (W × D × H)

CB-5120L Cabinet: Metal desk with storage capacity, approx. 55 cm × 51 cm × 34 cm (W × D × H)

¹ Requires PF-5120

² Bridge unit AK-5100 is required for the use of MT-5100, DF-5110, DF-5120

HyPAS™



*PanSolutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.